MODEL No. 328W COMPLETE WALK-ALONG TRACK

No. 328 SINGLE CARRIER
Neoprene-tired shielded ball bearing wheels riveted to formed steel body with swivel hook and trim chain. Nylatron glide strips reduce friction and noise. Supplied with 2 rubber bumpers. Zinc plated.

No. 349
WALK-ALONG MASTER CARRIER
2 Neoprene-tired shielded ball bearing wheel assemblies with swivel hook and trim chain pivot on steel connecting plate. Supplied with 2 rubber bumpers. Zinc plated.1 pair recommended for each walk-along curtain.

No. 306 CLAMP HANGER
Formed steel brackets clamp to track. Adjusts to any position. Suspend track with welded chain or wire rope. Zinc plated. 1 pair pictured.

No. 307 SPLICE
Steel plates align and lock track sections together. Track must be straight at joint. Zinc plated. 1 pair pictured.

No. 310 TRACK
6063-T5 extruded aluminum 1" wide x 2-1/2" high, .125" thick. Mill finish. 10', 20' and 24' stock lengths.

No. 311 CEILING HANGER
Steel plate mounts flush to ceiling. Track clamps to bracket with offset clips. Zinc plated.

No. 321 END STOP
Bolt with steel spacers to prevent carriers from traveling beyond desired location. For use with walk-along tracks. Zinc plated.

90 DEGREE TRACK CURVE
Factory bent with ends punched for splices. Each end has 12" straight section before curve begins for splicing.

No. 351 - 3'-4" radius
No. 352 - 4'-0" radius
No. 353 - 4'-8" radius
No. 354 - 5'-4" radius
No. 355 - 6'-0" radius
No. 356 - 6'-8" radius

Note: Optional accessory.

#328 SINGLE CARRIER **#349 WALK-ALONG MASTER CARRIER**

328W COMPLETE Walk-Along Track Standard Items

328	Single Carrier
349	Master Carrier
306	Clamp Hanger [1]
307	Splice [2]
321	End Stop
310	Track [2]

1 for ceiling mounted tracks use 311 Ceiling Hanger.
2 track lengths and splices supplied as required from stock sizes.