MODEL No. 328A
STANDARD-DUTY COMPLETE TRACK

Items shown for straight track, curved track requires addition of 318, 319 and 320 spindles and idler.

No. 328 SINGLE CARRIER
Neoprene-tired shielded ball bearing wheels riveted to formed steel body with swivel hook and trim chain. Nylatron glide strips reduce friction and noise. Supplied with 2 rubber bumpers. Zinc plated.

No. 329 MASTER CARRIER
2 Neoprene-tired shielded ball bearing wheel assemblies with swivel hook and trim chain pivot on formed steel body. Supplied with 2 clamps for anchoring operating line or cable. Supplied with 2 rubber bumpers. Zinc plated. 1 pair required for overlapping tracks.

No. 303 DOUBLE END PULLEY
4" diameter Nylatron GS sheaves with shielded ball bearings. Steel housing clamps to track. Zinc plated.

No. 304 SINGLE END PULLEY
4" diameter Nylatron GS sheave with shielded ball bearings. Steel housing clamps to track. Zinc plated.

No. 305 OVERLAP CLAMP
Formed steel clamps to align track at overlap. Zinc plated. 1 set pictured.

No. 306 CLAMP HANGER
Formed steel brackets clamp to track. Adjusts to any position. Suspend track with welded chain or wire rope. Zinc plated. 1 pair pictured.

No. 307 SPLICE
Steel plates align and lock track sections together. Track must be straight at joint. Zinc plated. 1 pair pictured.

No. 308 TENSION FLOOR BLOCK
4" diameter Nylatron GS sheave with shielded ball bearings. Spring in steel housing maintains line tension. Zinc plated.

No. 309
END STOP & CORD SUPPORT
Formed steel bracket bolts to track to support operating line and prevent carriers from traveling beyond desired location. Zinc plated. 1 pair required for overlapping tracks.

No. 301 TRACK
6063-T5 extruded aluminum 1" wide x 2-1/2" high, .125" thick. Mill finish. 10', 20' and 24' stock lengths.

No. 314 OPERATING LINE
1/4" diameter black polyester braided over Dyneema core for manual operation.

328A COMPLETE
Bi-Parting Track
Standard Items

328	Single Carrier
329	Master Carrier
303	Double End Pulley
304	Single End Pulley
305	Overlap Clamp [1]
306	Clamp Hanger [2]
307	Splice [2, 3]
308	Tension Floor Block
309	End Stop [1]
310	Track [3]
314	Operating Line

1 for bi-parting curtains only.
2 for ceiling mounted tracks use 311 Ceiling Hanger.
3 track lengths and splices supplied as required from stock sizes.

MODEL 328A TRACK

ELEVATION - MODEL 328A COMPLETE TRACK

PLAN - MODEL 328A COMPLETE TRACK

310 TRACK

328 SINGLE CARRIER

329 MASTER CARRIER

TRACKS AT CENTER OVERLAP

318 DOUBLE SPINDLE

319 SINGLE SPINDLE

311 CEILING CLAMP

320 OUTSIDE IDLER

304A SINGLE END PULLEY

304 SINGLE END PULLEY

303 DOUBLE END PULLEY