




Model No. 416W COMPLETE WALK-ALONG STEEL TRACK




No. 416 BLACK SINGLE CARRIER

2 nylon-tired ball bearing wheels riveted to black Super Tough nylon body with heavy-duty hook, swivel, and 6" trim chain for curtain attachment. Supplied with 1 No. 431 rubber bumper. Black finish.




No. 417 BLACK MASTER CARRIER

4 nylon-tired ball bearing wheels riveted to steel body. 2 clamps provided for anchoring operating line or cable. Supplied with 1 No. 431 rubber bumper. Black finish. 1 pair required for overlapping tracks.




No. 406 CLAMP HANGER

Formed steel brackets clamp to track. Adjusts to any position. Suspend track with welded chain or wire rope. Zinc plated. 1 pair pictured.




No. 407 SPLICE

Formed steel brackets align and lock track sections together. Zinc plated. 1 pair pictured.




No. 409 END STOP & CORD SUPPORT

Steel clamp with eye to support operating line and prevent carriers from traveling beyond desired location. Zinc plated. 1 pair required for overlapping tracks.



No. 410A TRACK

Mill finish 6063-T5 extruded aluminum 2-5/8" wide x 2-3/4" high, .080" thick. 20' and 24' stock lengths.




No. 410S TRACK

14 gauge galvanized steel, roll-formed to 2-5/8" wide x 2-3/4" high. 16', 20', 24', and 26' stock lengths.



416W COMPLETE Walk-Along Track Standard Items

- 416 Black Single Carrier
- 417 Black Master Carrier
- 406 Clamp Hanger¹
- 407 Splice^{1,2}
- 409 End Stop
- 410S Track²

1 not supplied for ceiling mount.
2 track lengths and splices supplied as required from stock sizes.
For aluminum substitute 410A for 410S.



410A TRACK
410S TRACK



416 BLACK SINGLE CARRIER AND 417 BLACK MASTER CARRIER