




MODEL No. 416P PREMIER STRAIGHT TRACK




No. 416 BLACK SINGLE CARRIER

2 nylon-tired ball bearing wheels riveted to black Super Tough nylon body with heavy-duty hook, swivel, and 6" trim chain for curtain attachment. Black finish.




No. 417 BLACK MASTER CARRIER

4 nylon-tired ball bearing wheels riveted to steel body. 2 clamps provided for anchoring operating line or cable. Black finish. 1 pair required for overlapping tracks.




No. 423 8" BLACK DOUBLE END PULLEY

8" diameter Nylatron GS sheaves with shielded ball bearings. Steel housing clamps to underside of track. Chain bracket for securing offstage curtain edge. Grooved for up to 1/2" operating line. Black finish.




No. 424 8" BLACK SINGLE END PULLEY

8" diameter Nylatron GS sheave with shielded ball bearing. Steel housing clamps to underside of track. Chain bracket for securing offstage curtain edge. Grooved for up to 1/2" operating line. Black finish.




No. 405 OVERLAP CLAMP

Formed steel clamps to align track at overlap. Zinc plated. 1 set pictured.




No. 406 CLAMP HANGER

Formed steel brackets clamp to track. Adjusts to any position. Suspend track with welded chain or wire rope. Zinc plated. 1 pair pictured.




No. 407 SPLICE

Formed steel brackets align and lock track sections together. Zinc plated. 1 pair pictured.




No. 422, BLACK 8" ADJUSTABLE FLOOR BLOCK

8" diameter Nylatron GS sheave with sealed precision ball bearings in heavy-duty steel housing with 9" vertical adjustment. Grooved to accept up to 1/2" operating line. Black finish.




No. 409 END STOP & CORD SUPPORT

Steel clamp with eye to support operating line and prevent carriers from traveling beyond desired location. Zinc plated. 1 pair required for overlapping tracks.




No. 410S TRACK

14 gauge galvanized steel, roll-formed to 2-5/8" wide x 2-3/4" high. 16', 20', 24', and 26' stock lengths.




No. 412A BLACK REAR FOLD GUIDE

Allows curtain to fold at offstage edges. Supplied with 1 rubber bumper. For use with 1/2" operating line. Black finish.



No. 420 OPERATING LINE

1/2" diameter black spun polyester braided over solid polyester core for manual operation.



No. 421 CLAMP HANGER WITH IDLER

No. 406 clamp hanger with Nylatron GS ball bearing roller for supporting operating line or cable. Zinc plated.


416P COMPLETE Bi-Parting Track Standard Items

- 416 Black Single Carrier
- 417 Black Master Carrier
- 423 Black 8" Double End Pulley
- 424 Black 8" Single End Pulley
- 405 Overlap Clamp^{1,2}
- 406 Clamp Hanger²
- 407 Splice^{2,3}
- 412A Black Rear Fold Guide
- 422 Black 8" Adj. Floor Block
- 409 End Stop¹
- 410S Track³
- 420 1/2" Operating Line
- 421 Clamp Hanger w/ Idler


- 1 for bi-parting curtains only.
- 2 not supplied for ceiling mount.
- 3 track lengths and splices supplied as required from stock sizes.




MODEL 416P PREMIER TRACK




PLAN - 416P COMPLETE TRACK




ELEVATION - 416P COMPLETE TRACK





410S TRACK




TRACKS AT CENTER OVERLAP



416 BLACK SINGLE CARRIER, 417 BLACK MASTER CARRIER AND 421 CLAMP HANGER WITH IDLER



424 BLACK 8" SINGLE END PULLEY



423 BLACK 8" DOUBLE END PULLEY

