




MODEL No. 516W COMPLETE WALK-ALONG TRACK



No. 516 SINGLE CARRIER


2 nylon-tired sealed ball bearing wheels riveted to plated steel body with heavy-duty hook, swivel and 6" trim chain. Nylatron glide strips and rubber bumper reduce friction and noise. Zinc plated.



No. 517W


WALK-ALONG MASTER CARRIER

2 single carriers pivot on steel connecting plate with heavy-duty hook, swivel and trim chain. Nylon-tired wheels. Zinc plated.




No. 506 CLAMP HANGER

Formed steel bracket for suspending track. Track clamps to bracket with offset clips. Zinc plated.




No. 507 SPLICE

Steel plates align and lock track sections together. Track must be straight at joint. Zinc plated. 1 pair pictured.




No. 509 END STOP

Bolt with steel spacers to prevent carriers from traveling beyond desired location. Zinc plated. 2 pair required for overlapping tracks.



No. 510 TRACK

6063-T5 extruded aluminum 1-5/8" wide x 3-1/4" high, .187" thick. 20' and 24' stock lengths. Mill finish.




No. 531 FLUSH CEILING HANGER

Steel plate mounts flush to ceiling. Track clamps to bracket with offset clips. Zinc plated. For use on walk-along tracks only.


516W COMPLETE Walk-Along Track Standard Items

- 516 Single Carrier
- 517W Master Carrier
- 506 Clamp Hanger¹
- 507 Splice²
- 509 End Stop
- 510 Track²

- 1 substitute 531 for ceiling mount.
- 2 track lengths and splices supplied as required from stock sizes.



No. 531 FLUSH CEILING HANGER



No. 516 SINGLE CARRIER AND 517W WALK-ALONG MASTER CARRIER