




MODEL No. 516C COMPLETE CURVED TRACK

For motorized operation




No. 516 SINGLE CARRIER

2 nylon-tired sealed ball bearing wheels riveted to plated steel body with heavy-duty hook, swivel and 6" trim chain. Nylatron glide strips and rubber bumper reduce friction and noise. Zinc plated.




No. 517M MASTER CARRIER

2 nylon-tired sealed ball bearing wheel assemblies pivot on formed steel body with 2 clamps for anchoring line or cable. 1 pair required for overlapping tracks. Zinc plated. For 3/16" operating cable.




No. 503M DOUBLE END PULLEY

6" diameter Nylatron GS sheaves with sealed precision ball bearings. Heavy-duty steel housing clamps to top flange of track. Zinc plated. Grooved for 3/16" operating cable.




No. 504M SINGLE END PULLEY

6" diameter Nylatron GS sheave with sealed precision ball bearings. Heavy-duty steel housing clamps to top flange of track. Zinc plated. Grooved for 3/16" operating cable.




No. 505 OVERLAP CLAMP

Formed steel clamps to align track at overlap. Zinc plated. 1 set pictured.




No. 506 CLAMP HANGER

Formed steel bracket for suspending track. Track clamps to bracket with offset clips. Zinc plated.




No. 507 SPLICE

Steel plates align and lock track sections together. Track must be straight at joint. Zinc plated. 1 pair pictured.




No. 509 END STOP

Bolt with steel spacers to prevent carriers from traveling beyond desired location. Zinc plated. 2 pair required for overlapping tracks.




No. 510 TRACK

6063-T5 extruded aluminum 1-5/8" wide x 3-1/4" high, .187" thick. 20' and 24' stock lengths. Mill finish.



No. 515 OPERATING CABLE

Black polyester jacket braided over 3/32" specialty cord wire rope. For use with motorized tracks.



No. 518 CABLE GUIDE

3 Nylatron GS rollers mounted to steel bracket. Bracket mounts to track with offset clips. Suggested spacing: 5'. Additional guides required at each curve. 5/16" shielded ball bearings. Zinc plated.


501C COMPLETE Bi-Parting Track Standard Items

- 516 Single Carrier
- 517M Master Carrier
- 503M Double End Pulley
- 504M Single End Pulley
- 505 Overlap Clamp
- 506 Clamp Hanger¹
- 507 Splice²
- 509 End Stop
- 510 Track²
- 515 Operating Cable
- 518 Cable Guide


- 1 substitute 511 for ceiling mount.
- 2 track lengths and splices supplied as required from stock sizes.




MODEL 516C TRACK




PLAN - 516C COMPLETE TRACK




ELEVATION - 516C COMPLETE TRACK




510 TRACK




518 CABLE GUIDE





TRACKS AT CENTER OVERLAP




504M SINGLE END PULLEY




503M DOUBLE END PULLEY



506 & 511 TRACK HANGERS



516 SINGLE CARIER



517M MASTER CARRIER