




MODEL No. 501SB BLACK COMPLETE STRAIGHT TRACK

For motorized operation




No. 501B BLACK SINGLE CARRIER

2 urethane-tired sealed ball bearing wheels riveted to plated steel body with heavy-duty hook, swivel and 6" trim chain. Nylatron glide strips and rubber bumper reduce friction and noise. Black finish.




No. 502MB BLACK MASTER CARRIER

2 urethane-tired sealed ball bearing wheel assemblies pivot on formed steel body with 2 clamps for anchoring line or cable. 1 pair required for overlapping tracks. Black finish. For 3/16" operating cable.




No. 503MB BLACK DOUBLE END PULLEY

6" diameter Nylatron GS sheaves with sealed precision ball bearings. Heavy-duty steel housing clamps to top flange of track. Black finish. Grooved for 3/16" operating cable.




No. 504MB BLACK SINGLE END PULLEY

6" diameter Nylatron GS sheave with sealed precision ball bearings. Heavy-duty steel housing clamps to top flange of track. Black finish. Grooved for 3/16" operating cable.




No. 505B BLACK OVERLAP CLAMP

Formed steel clamps to align track at overlap. Black finish. 1 set pictured.




No. 506B BLACK CLAMP HANGER

Formed steel bracket for suspending track. Track clamps to bracket with offset clips. Black finish.




No. 507B BLACK SPLICE

Steel plates align and lock track sections together. Track must be straight at joint. Black finish. 1 pair pictured.




No. 509B BLACK END STOP

Bolt with steel spacers to prevent carriers from traveling beyond desired location. Black finish. 2 pair required for overlapping tracks.




No. 510-B BLACK TRACK

6063-T5 extruded aluminum 1-5/8" wide x 3-1/4" high, .187" thick. 20' and 24' stock lengths. Class 1 black anodized.



No. 515 OPERATING CABLE

Black polyester jacket braided over 3/32" specialty cord wire rope. For use with motorized tracks.



No. 518B BLACK CABLE GUIDE

3 Nylatron GS rollers mounted to steel bracket. Bracket mounts to track with offset clips. Suggested spacing: 5'. Additional guides required at each curve. 5/16" shielded ball bearings. Black finish.


501SB Black COMPLETE Bi-Parting Track Standard Items

- 501B Black Single Carrier
- 502MB Black Master Carrier
- 503MB Black Double End Pulley
- 504MB Black Single End Pulley
- 505B Black Overlap Clamp
- 506B Black Clamp Hanger¹
- 507B Black Splice²
- 509B Black End Stop
- 510-B Black Track²
- 515 Operating Cable
- 518B Black Cable Guide


- 1 substitute 511B for ceiling mount.
- 2 track lengths and splices supplied as required from stock sizes.




MODEL 501SB BLACK TRACK




PLAN - 501SB BLACK COMPLETE TRACK




ELEVATION - 501SB BLACK COMPLETE TRACK




510-B BLACK TRACK




518B BLACK CABLE GUIDE




TRACKS AT CENTER OVERLAP




504MB BLACK SINGLE END PULLEY




503MB BLACK DOUBLE END PULLEY



506B & 511B BLACK TRACK HANGERS



501B BLACK SINGLE CARRIER



502MB BLACK MASTER CARRIER

