# MODEL 818-1 COMPLETE WALK-ALONG TRACK

**No. 818 SINGLE CARRIER**
2 urethane-tired shielded ball bearing wheels fastened parallel to carrier body. Nylatron GS nylon shall be molded around shielded and greased ball bearing to form carrier body with integral glides to keep carrier aligned at all times. Supply with heavy duty hook, swivel eye, trim chain for attachment of curtain and rubber bumper.

**No. 807 BAR SPLICE**
Steel brackets for aligning "C" channels. With all necessary hardware.

**No. 807P BATTEN SPLICE**
Steel tube splice for backbone. With all necessary hardware.

**No. 818-1 TRACK**
Track shall be constructed of carrier rails roll-formed from 16 gauge galvanized steel into 1" x 5/8" "C" channel. Two rails shall be suspended from 1-7/8" O.D. tubing backbone on 2'-0" intervals by steel hanger assemblies creating a 3/4" continuous slot for passage of carrier bodies.

**No. 809 END STOP**
Steel clamp with eye for securing offstage edge of curtain and prevent carriers from travelling beyond desired location.

**818-1 COMPLETE Walk-Along Track Standard Items**

| | |
|---|---|
| 818 | Single Carrier |
| 807 | Splice [1] |
| 809 | End Stop |
| 818-1 | Track [1] |

1 track length and splices supplied as required from stock sizes.

## MODEL 818-1 TRACK

**818-1**

**TRACK SPLICE**

**818 SINGLE CARRIER**